



MOTION PRO, INC.
3171 Swetzer Road
Loomis, CA 95650
Tel 650.594.9600 Fax 650.594.9610
www.motionpro.com

MSDS

MATERIAL SAFETY DATA SHEET

Material Safety Data Sheet for Motion Pro Cable Lube Part# 15-0001 & 15-0002

PRODUCT TRADE NAME: **MOTION PRO CABLE LUBE #15-0002**
REVISION DATE: December 1, 2018
CHEMICAL NAME: Mixture
NFPA CODE: Health: 1 Fire: 1 Reactivity: 0

SECTION 1 - HAZARDOUS INGREDIENTS

None
This material does not contain any chemical listed as a carcinogen or potential carcinogen by OSHA, IARC Monographs, or National Toxicology program at a concentration > 0.1%.

SECTION 2 - FIRE AND EXPLOSION HAZARDS

FLASH POINT: 370°F
UPPER FLAMMABLE LIMIT: Not Determined.
LOWER FLAMMABLE LIMIT: Not Determined.
EXTINGUISHING MEDIA: CO₂, dry chemical, foam.
SPECIAL FIRE FIGHTING PROCEDURES: None
UNUSUAL FIRE & EXPLOSION HAZARDS: None

SECTION 3 - HEALTH HAZARD DATA

ORAL TOXICITY: Greater than 5000 mg/kg in rats. Based on data from components.
EYE IRRITATION: May cause mild eye irritation.
SKIN IRRITATION: May cause mild skin irritation.
OTHER: Unknown.
TLV: None established. Oil mist TLV 5mg/m³.

FIRST AID PROCEDURES

SKIN: Wash well with soap and water.
EYE: Flush well with water.
INHALATION: Remove to fresh air. See a physician if irritation persists.
ORAL: Call a physician. Give two glasses of water and induce vomiting.
ADDITIONAL: None.

SECTION 4 - SPECIAL PROTECTION INFORMATION

VENTILATION PROCEDURE: Mechanical ventilation recommended.
GLOVES PROTECTION: Neoprene or nitrile rubber gloves recommended.
EYE PROTECTION: Safety glasses.
OTHER PROTECTION: Long-sleeved shirt

SECTION 5 - PHYSICAL DATA

VAPOR PRESSURE: Not Determined
SPECIFIC GRAVITY: 0.98
WATER SOLUBILITY: Insoluble
PERCENT VOLATILE: Not Determined.
VAPOR DENSITY: Not Determined.
EVAPORATION RATE: Not Determined.
ODOR: Mild.
APPEARANCE: Light-colored oily liquid.



MOTION PRO, INC.
3171 Swetzer Road
Loomis, CA 95650
Tel 650.594.9600 Fax 650.594.9610
www.motionpro.com

MSDS

MATERIAL SAFETY DATA SHEET

Material Safety Data Sheet for Motion Pro Cable Lube Part# 15-0001 & 15-0002

SECTION 6 - STABILITY

STABILITY: Stable
INCOMPATIBILITY: Oxidizing agents
POLYMERIZATION: Will not occur.
THERMAL DECOMPOSITION: Oxides of carbon.

SPILL OR LEAK PROCEDURES

SPILL PROCEDURES: Prevent entry into sewers and waterways. Pick up free liquid for disposal. Absorb small amounts on inert material for disposal.
WASTE DISPOSAL: If disposed of, this material is not believed to be a characteristic hazardous waste under RCRA. Disposal should be in compliance with federal, state, and local laws.

SPECIAL PRECAUTIONS

SPECIAL PRECAUTIONS: Store in a cool, dry, place away from flame. Remove contaminated clothing and launder before reuse.

TRANSPORTATION AND LABELING

DOT Surface Shipping Description: Consumer Commodity, ORM-D
After 1/1/2014 UN1950, Aerosols, 2.1 Ltd. Qty (Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)

Canadian TDG Classification: Limited Quantity

IMDG Code Hazard Classification: UN1950, Aerosols, 2.1.

The information presented herein has been compiled from sources considered dependable and is accurate to the best of Motion Pro's knowledge; however, Motion Pro makes no warranty whatsoever, expressed or implied, of merchantability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. Motion Pro assumes no responsibility for injury to recipient or to third persons or for any damage to any property and buyer assumes all such risks.